



**DESCRIPTION**

Aluminium stair-nosing with anti-slip carborundum insert. To secure stairs and reduce slip risk. 18 holes, first and last one at 83 mm.

Supplied with 36 mm black adhesive insert. Non fitted  
 Drilled - countersunk: to be screwed  
 Dim. : 67 x 32 mm  
 Length : 3 M

**USE**

For overlapping a floor covering or a parquet or concrete floor.

**REFERENCE**

- **1390**  
STAIRNOSING BEVEL ALU SILVER 36MM +INS NOT FIT 3M

**MATERIAL**

Alu silver - REACH compliant.  
 For available inserts, see ROMUS catalogue

**INSTALLATION PROCESS**

Cut the profile to the desired length. Locate the holes and drill into the concrete. Place the ROMUS plugs 94154. Position the profile and fasten with screws 94136. Make the aluminium profile free of grease, by using isopropylic alcohol. Remove the silicone-coated backing paper and fix the anti-slip insert. Press with roller 95137.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Phone :

Email :

Project :

Distributor :

Phone :

Email :