



USE

To be applied just before gluing **ONLY** on concrete surfaces (200-400g/m² depending on porosity), porous and coated natural stone (200g/m²).

ACTISOL should not be used on smooth, non-porous surfaces such as metal, tiling, old paints and asphalt.

DESCRIPTION

A (slightly bluish) liquid activator to be applied with the 500ml spray bottle to the area intended to accommodate the rail and the glued tactile tile. The surface must appear moist before the tactile component is installed. The activator is designed to enhance the effectiveness of the adhesive.

Capacity of the spray bottle: 500ml

DENSITY: 0,87 +/- 0.05

FLASH POINT: > 29°C

STORAGE AND LIFESPAN: Four years in unopened original packaging protected from freezing temperatures and high heat.

HYGIENE AND SAFETY: Flammable product.

Observe all precautions for use.

INSTALLATION GUIDELINES

ACTISOL is to be applied using the 500ml spray bottle. Adjust the spray volume using the adjustment knob so that the spray is delivered in microdroplets. Apply only to the area where the adhesive is to be applied. However, ACTISOL may extend beyond the areas where the tiles and rails are to be installed without any consequences either for the surface or for the tiles and rails already in place.

ACTISOL should be used only at the time of gluing and not in advance. The surface must appear moist when the adhesive is being applied.

Quantity:

- On asphalt: 200g/m²

- On concrete depending on its porosity: 200-400g/m²

Warning: overapplication of ACTISOL will result in an increase in the time required to put the products with the adhesive fastening back into service. ACTISOL will take longer to evaporate.

The information contained in this document is provided for information purposes only. ROMUS cannot be held liable for any inaccuracies in this information. The user or specifier will check the compatibility of the product technical data with the actual situation. ROMUS reserves the right to modify all or part of this document without prior notice.

Architect:

Tel.:

E-mail:

Project:

Distributor:

Tel.:

E-mail: