

Technical Data Sheet - GB



- The **MTA METHACRYLATE adhesive** is intended for attaching products to the floor to assist with the movement of the visually impaired and the blind.

Due to its methacrylate nature, it is optimally compatible with **“EXTELINE” TACTILE TILES** and **EXTELINE STRIPS**.

The **MTA METHACRYLATE adhesive** allows for very efficient bonding in areas with moderate traffic.

- **Preparing the surface:**

- **On hydrocarbon coating:**

- The surface must be clean, dry and free of non-adherent material (dust, grit, grease, oil, etc.). On a new coating, application must be made at least one month after its completion, until it is completely free of dye bleeding.

- **On concrete and cement:** First apply our MTA primer.

- **Conditions for application:**

To ensure proper adhesion, the surface must be:

- Dry
 - Clean
 - Cohesive
 - Free of oils.

At a temperature from +5°C to +35°C and a relative humidity of less than 80%.

Technical Data Sheet - GB

- **1) Mix** thoroughly the base and hardener using an electric mixer, to be applied with a notched trowel. Apply to the surface meant to receive the "EXTELINE" TACTILE TILE or the EXTELINE STRIP.

Be sure not to exceed the dimensions of the product to be glued. Practical mixing time is 15 minutes at 20 °C.



with an increase in the ambient temperature, the usage life of the mixture decreases.

- **Standard Packaging:** Metal bucket with 8kg net
- **Storage:** The MTA Adhesive can be stored 6 months in its original, unopened container, away from heat and extreme cold.
- **Health and safety.**

- Dirty packaging and cleaning products are Special Industrial Waste to be treated according to the regulations in force.

- Contains Organic Peroxide.

- Product is highly flammable.

- **Application with:**



Glue trowel:

TKB teeth: B15 which is 1500/gm².

TECHNICAL SPECIFICATIONS

| | |
|-----------------------|----------------|
| Binding: | Methacrylic |
| Density XP-P-98 633 | 1.9kg/l |
| Asquer LCPC PMA-ME5 | 100% |
| Appearance | |
| Consumption: | |
| Tactile Tiles 42 x 04 | 3 kg / tile |
| Guide strip | 1.5 kg / strip |

Architect/Investor:
Project:
Email:
Tel:

Distributor:

Tel:

Email: