


APPLICATION INSTRUCTIONS

Anti-Slip always provides an anti-slip surface that is:

- Durable
- Efficient
- Effective

But for best results follow the instructions below to ensure maximum performance in all environments.



1) Material Storage

Ensure the material is kept in dry, warm conditions in the original protective packaging.

2) Surface Preparation

A clean, dry surface is essential. Use a cleaner to remove all surface contaminants (paint flakes, etc) - DO NOT use methylated spirits/ petrol/ lighter fluid etc as these leave behind a thin, greasy residue. Ensure prepared surface is above 10°C.

3) Porous Surface Sealing

Porous surfaces must be sealed prior to application to prevent water attacking the adhesive. Toluene based primers are ideal - we recommend our Surface Primer for this job. Apply a thin coat to the cleaned surface using a paint brush, then leave to dry.

4) Tape Application

Peel back part of the release liner then press the adhesive firmly onto the prepared surface, and slowly keep peeling back the liner while applying the tape. Try to ensure that the tape is not taut.

5) Finish!

Once applied, press tape down firmly using even pressure (decorating rollers are excellent for this). We recommend sealing the edges using 'Edge Fix' as this will extend the life of the

product. Only use a small amount down the edges, a thin bead.

If correctly applied, the new anti-slip surface can be walked on instantly, you will get maximum benefit from the adhesive system after 48 hours.

We always recommend the use of anti-slip Primer & anti-slip joint to help with the service life of our Anti-Slip tape.

ANTI-SLIP PRIMER 500ml ref 6992



Our Primer anti-slip is ideal for sealing porous surfaces such as wood, concrete or stone prior to application of our Anti-Slip; it also greatly helps to create an extra bond on other surfaces. The normal tin size is 1 litre which covers approximately 5m², It is simply brushed into place.

ANTI-SLIP JOINT 140ml ref 6993

Anti-slip Joint greatly helps to prevent the lifting of the Anti-Slip in high traffic areas. One simply applies the sealant down the side of the tape using the narrow nozzle built into the tube, it helps to secure the product and extend its life. A 140ml tube will cover approximately 35 linear metres. Only a very small amount is required for bonding the edges of our grip tape.

