

## TECHNICAL SHEET\_GB

Ref. 8821/8822



### How to order a logo mat?

- 1- We send the design of the logo ideally in digital file. Ai eps or pdf or high definition.
- 2- specify if the carpet is installed flat on the floor or in a pit. If in a pit pass additional order in 8851 Ref.
- 3- tell us the background color and dimensions of the carpet.
- 4- we send you by email within 48 hours and free model for acceptance.
- 5- We manufacture the carpet under about 15 days after acceptance of the model.

Professional carpet made from:

- Tufted textile polyamide fibers 6 .6bicolores and twisted shape to absorb maximum dust
- Sole 100% thick rubber reinforced edges for better tear resistance and to improve the stability of the carpet
- Antistatic
- High UV resistance
- A washing machine

Weight	2450g/m <sup>2</sup>
Height fiber	7 mm
Thickness borders	2.1 mm
water absorption	6 à 7 l/m <sup>2</sup>
din tolerance.	+/- 5 cm
fire classification	Cfl-s1

### SIZE STANDARD

#### Dimensions

85 x 150 cm	8821
115 x 180 cm	8822

### SIZES TO MEASURE

#### Width

85 to 115 cm	8827
116 to 150 cm	8828
151 to 200 cm	8829

*Les informations contenues dans ce document sont communiquées à titre indicatif. Elles ne peuvent engager la responsabilité de ROMUS. L'utilisateur ou le prescripteur vérifiera la compatibilité des données techniques du produit avec la situation réelle. La société ROMUS se réserve le droit de modifier tout ou une partie de ce document sans préavis.*

Architecte:

Projet:

Email:

Tél:

Distributeur:

Tél:

Email:

### SPECIFICATION TECHNIQUE

TEXTILE		SOLE		
Fiber Type	Polyamide 6.6	Construction - folder elementary	Non-woven polyester	
Under the strand	1365 Dtex	Composition of the sublayer	100% nitrile rubber	
textile finishing	Velvet	finishing option	Sole smooth / supplement carpet ref pit. 8851	
textile construction	Tuft online	Types of sole	Standard	3.0 mm
Textile Height	8.5 mm	Weight of sole gr / m <sup>2</sup> -tolerance +/- 5%	1376	3776
Point density	155 000 points pa m <sup>2</sup>	Thickness of the sole	1.1 mm	3.0 mm
dye technology		Thicknesses borders	2.1 mm	3.0 mm
Textile Weight (approx.)	965 g/m <sup>2</sup>	Border width	18 mm	
		Perforation insole Energie®	Yes	No

FINAL PRODUCT		
Sole Type	standard	3.0 mm
Total weight of the carpet gr. (Approx.)	2450 gr/m <sup>2</sup>	4675 gr/m <sup>2</sup>
85x120 cm	2510	4760
85x150 cm	3120	5960
85x300 cm	6200	11940
115x180 cm	5020	9700
115x240 cm	6670	12950
150x250 cm	9020	17630
200x200 cm	9800	18700

TEST	
color fastness to washing (discoloration and stains)	According to test ISO 105-A04: ranking 3
antistatic	Antistatic according to your ISO 14041
fire classification	Ranking Cn-s1 - ISO 13501 test