

### TECHNICAL SHEET\_GB

#### ROCLEAN



steel gray



Mink



#### DESIGN

Professional carpet made from:

- Tufted textile polyamide fibers 6 bicolor and twisted shape to absorb maximum dust
- Sole 100% thick rubber reinforced edges for better tear resistance and to improve the stability of the carpet
- antistatic
- High UV resistance
- A washing machine. Fire classification Efl

Weight	2260g/m <sup>2</sup>
Height fiber	7 mm
Thickness borders	2.1 mm
water absorption	6 à 7 l/m <sup>2</sup>
fire classification	Efl

#### SIZE STANDARD

Dimensions	steel gray	Mink
85 x 150 cm	8840	8841
115 x 180 cm	8845	8846

#### SIZES TO MEASURE

Width	steel gray	Mink
85 à 115 cm	8837	8834
116 à 150 cm	8838	8833
151 à 200 cm	8839	8832

Les informations contenues dans ce document sont communiquées à titre indicatif. Elles ne peuvent engager la responsabilité de ROMUS. L'utilisateur ou le prescripteur vérifiera la compatibilité des données techniques du produit avec la situation réelle. La société ROMUS se réserve le droit de modifier tout ou une partie de ce document sans préavis.

Architecte:

Projet:

Email:

Tél:

Distributeur:

Tél:

Email:

## TECHNICAL SPECIFICATION

TEXTILE	
Fiber Type	Polyamide 6
Under the strand	1350 Dtex
textile finishing	Velvet
textile construction	Tuft online
Textile Height	10 mm
Point density	Approx. 76,000 points per m <sup>2</sup>
dye technology	dyed
Textile Weight (approx.)	760g/m <sup>2</sup>

SOLE		
primary-Construction Dossier	Polyester nonwoven	
Composition of the underlayer	100% nitrile rubber	
finishing option	Uppers pit /carpet supplement	
Types of sole	standard	3 mm
total weight of the carpet in gr / m <sup>2</sup> Tolerance +/- 5%	2260	4480
the rubber sole of mass in gr / m <sup>2</sup> (body belt)	1376	3776
Thickness of the sole	1.1 mm	3.0 mm
Thickness borders	2.1 mm	3.0 mm
Border width	18 mm	
Perforation-sole Energie®	YES	NO

FINAL PRODUCT		
Sole Type	Standard	3.0 mm
Total weight of the carpet gr. (Approx.)		
85x120 cm	2310	4570
85x150 cm	2880	5710
85x300 cm	5710	11450
115x180 cm	4620	9300
115x240 cm	6140	12410
150x250 cm	8280	16890
200x200 cm	9040	17920

TEST	
color fastness to washing (discoloration and stains)	Rank 5 test according ISO 105-A04
color UV resistance	Rank 8 test according ISO 105-B02
antistatic	Antistatic according to ISO 14041 test
fire classification	According to ISO 13501 test fire class Efl