

QUICK TRIO Ref 8870 - 8871

TECHNICAL DATASHEET - GB





By the roll: Dimensions of a full roll: Length of stripes (L) 2m x Walking Direction (W.D) 10 m

To be cut: - Can only be ordered by mat width (walking direction) W. -

The minimum order is 2m in length (fixed) x 1m in walking direction, but beyond that, mats are invoiced to the exact width ordered. - Can be cut to order on site using an angle grinder for aluminium and carpet knife.

3 strips of different nature = higher efficiency



CONCEPTION

QUICK TRIO is a revolutionary heavy duty washable entrance mat made of 90% of polypropylene and 10% of polyamide, in 3 strips.

- The first strip is a polyamide brush for heavy scraping of coare dirt.
- The second one is a polypropylene needle felt strip scraping finer dirt (sand etc.)
- The third one is a polyamide strip absorbing moisture.

UV RESISTANT

TECHNICAL DATA

| Weight | 2.75 kg/m ² |
|------------------|------------------------|
| Total thickness | 13 mm |
| Sublayer | 3 mm latex |
| Fire rating | EFL |
| Water absorption | 3-4L/m2 |
| Electrostatic | < 2 KV |

LIGHT RESISTANCE

Color stability to light: > 5

Color stability to water: 5

Color stability to sea water : 5

Color stability to friction: 4/5

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information.

The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect: Project: Email: Tel: