

**TECHNICAL DATASHEET- GB****DESCRIPTION**

One component sealant based on a mixture of synthetic resins in dispersion. Exempt of solvents and silicones.

**APPLICATION**

Specially indicated for sealing joints, skirting boards of wooden floors (parquet, floating platforms etc.) wood carpentry (built-in cupboards, windows, doors, etc.)

This product is compatible with paints and varnishes and does not damage the adherence and smoothness of the varnishes.

Surfaces must be clean and free of grease. Do not use in joints with a deformation level higher than 10%.

Depending on room temperature, the product can be varnished approximately 1 hour after application.

**TECHNICAL CHARACTERISTICS**

<b>CHARACTERISTIC</b>	<b>Unit</b>	<b>Value</b>
Aspect		Pasty
Modulus (100%)	N/mm <sup>2</sup>	0.09
Elongation at break	%	1184
Tensile strength	N/mm <sup>2</sup>	0.12

**STORAGE AND SHELF LIFE**

Store in a fresh and dry place. Recommended storage temperature between +5°C and +35°C. 60 months in original unopened packaging. Storage between +5°C and +30°C

**PACKAGING**

310 ml cartridge, 12 units per box.

# ROMUS

## ® COLOUR SEALANT

Ref. 94709-94718-94780-94781-94782-  
94783-94784-94786-94997-94998

### TECHNICAL DATASHEET- GB

#### CAUTION

Consult the material safety data sheet for more information.

#### NOTE

In case of doubt, please consult our technical department, which will suggest the right product for your work or conduct testing to find it.

The technical information contained in this document, as well as our technical advice whether verbal or written, is the result of our experience with the product and should be considered as collaboration without compromise, since the use and / or final application of our adhesives is beyond our control, declining all liability for improper use. The customer is responsible to confirm and evaluate prior to use, by trial or test the product conforms to required employment.

So our guarantee is limited to ensure the quality of our products, according to our quality standards.