

TECHNICAL SHEET



Application

double-sided film used in many applications for securing lightweight objects, samples or felt pieces.

Advantages

- **synthetic rubber adhesive:**
 - High tack and high adhesiveness on both sides.
 - Good adhesion on different surfaces
- **Support PP cast:**
 - Fort extension
 - Good adaptation to different shapes.
 - Easy use.

* Our products should be tested without the actual use before any industrial use. The shelf life and storage is 12 months, based on the product stored at 23 ° C and 50% relative humidity in the sun.

Technical data

Support	Film PP cast 50μ, transparent
Adhesive	Synthetic rubber, white
Protective	silicone paper double-sided color honey
Total thickness (without liner)	115μ
Adhesion to steel	outer face: 20N/25mm inner side: 25N/25mm
Strength at break MD	50N/25mm
Elongation at break	600 %
Temperature resistance	60°C

Ref.	Type	dimensions
98000	Polypropylène	50 mm x 5m
98020		50 mm x 25 m
98040		100 mm x 25 m

Les informations contenues dans ce document sont communiquées à titre indicatif. Elles ne peuvent engager la responsabilité de ROMUS. L'utilisateur ou le prescripteur vérifiera la compatibilité des données techniques du produit avec la situation réelle. La société ROMUS se réserve le droit de modifier tout ou une partie de ce document sans préavis.

Architecte:

Projet:

Email:

Tél:

Distributeur:

Tél:

Email: