ROMUS

«ROMTACK» RUBBER TILES Réf. 98275

Technical Data Sheet - Uk



Dimensions : 240 mm x 50 m

Physical Chemical Properties		
Form :	solid	
Color :	clear	
Odor :	typically acrylic	

Double-sided reinforced adhesive transfer tape, aggressive adhesion.

TECHNICAL	DATA
Carrier :	polyester-thread
Thickness of carrier :	0,100 mm
Total thickness without liner :	0,230 mm
Total thickness with liner :	0,310 mm
Thickness of liner :	0,080 mm
Adhesive :	solvent free, acrylate-dispersion
Colour of adhesive :	transparent
Resistance to plasticizer migration :	very good
Ageing resistance :	very good
Resistance to condensation water :	good
Heat resistance (short-term) :	+120° C
Cold resistance :	-30° C
Processing temperature :	+10° C

Details to the product : Acrylic based transfer tape with paper liner, PETP-scrim.

Composition/ Information on Ingredients :

Common Chemical Name : Adhesive on acrylic base Hazardous Ingredients : None

Fire Fighting Measures : Waterfog, foam, CO2 or dry media

Accidential Release Measure :

Spill or Leak Procedures : Put into suitable container for disposal as none hazardous waste. Neutralizing Chemicals : None required Special Precautions : None

Handling and Storage :

Storage : Normal Roomtemperature 50 % rel. Humidity.

Exposure Controls / Personal Protection :

Personal Protective Equipment Eye : Glasses Skin : Protect Skin by wearing long shirts and pants. Respiratory Protection: None

Toxicological Information : Not Toxic

Ecological Information :

This material is not toxic to animals, plants or fish.

Architecte/Entreprise :			
Projet :			
Email :			
Tel:			
Distributeur :	Tel :	Email :	