DATA SHEET

> MAINTENANCE

Pour l'entretien journalier, utiliser des produits nettoyants standards. Dans l'hypothèse d'utiliser un produit à base de soude, d'ammoniaque ou d'acide, faire un essai préalable.

DESCRIPTION

Profilé inox percé
pour réaliser une jonction entre 2 revêtements de niveaux identiques
A visser - Perçage central
14 trous, avec le premier et le dernier à 83 mm

USE

Se pose en recouvrement d'un revêtement de sol ou d'un parquet
Utilisation en intérieur

REFERENCE

Ref : 1216

MATERIAL

Acier inoxydable fabriqué par les meilleurs spécialistes dans les épaisseurs convenables. Il est du type 1.4016 recuit «poli miroir» pour tous les profils sauf les cornières adhésives qui sont du type «alimentaire», 1.4509.
Conformité REACH

FITTING MODE

Couper le profilé à la longueur souhaitée. Repérer les trous et percer dans la chape. Placer les chevilles ROMUS 94154. Placer le profilé et visser avec les vis VVVV.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :