DATA SHEET

> MAINTENANCE

Pour l'entretien journalier, utilisez des produits nettoyants standards. Dans l'hypothèse d'utiliser un produit à base de soude, d'ammoniaque ou d'acide, faire un essai préalable.

DESCRIPTION

Profilé aluminium perçé pour réaliser une jonction entre 2 revêtements de niveaux identiques.
Percé - fraisé : à visser. Les trous sont percés, fraisés puis ébavurés par-dessous.
Conditionnement : Sous gaine de protection avec vis et chevilles. Livré avec vis et chevilles.

Hauteur : 5 - 11,5 mm
Largeur : 34 mm
Longueur : 2,70 M

USE

Se pose en recouvrement d'un revêtement de sol ou d'un parquet. Utilisation en intérieur.

REFERENCE

Ref : 3410

MATERIAL

Alu incolore.
Conformité REACH

FITTING MODE

Positionnez la base du profilé en respectant un espace pour dilatation. Repérez les trous et percer dans la chape. Placez les chevilles, vissez la base. Vissez le chapeau sur la base pour assurer une bonne jonction.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :