


DATA SHEET



DESCRIPTION

Aluminium stair-nosing with anti-slip PVC insert
 For all public places or areas of heavy traffic (offices, schools, hospitals, underground, stores etc...)
 To secure stairs and reduce slip risk
 Drilled - countersunk: to be screwed
 18 holes, first and last one at 83 mm
 Holes are drilled, countersunk and deburred
 For available inserts, see ROMUS catalogue

USE

To be installed in junction with a floor covering
 Indoor use

REFERENCE

Ref : 1670

MATERIAL

REACH compliant
 Polyurethane insert fire rating: Bs2 d0

FITTING MODE

Cut the profile to the desired length. Locate the holes and drill into the concrete. Place the ROMUS plugs 94154. Position the profile and fasten with screws 94136. Make the aluminium profile free of grease, by using isopropyl alcohol. Remove the silicone-coated backing paper and fix the anti-slip insert. Press with roller 95137.

> MAINTENANCE

For daily cleaning, use standard detergents. In case you want to use a sodium, ammoniac or acid based cleaner, carry first out a preliminary test on the profile, avoiding the insert.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :



- ▶ STAIR-NOSINGS
- ▶ "TECNIROMUS" HEAVY TRAFFIC
- ▶ AS 11 REF. 1670

DATA SHEET

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :