

## DATA SHEET

### > MAINTENANCE

Pour l'entretien journalier, utiliser des produits nettoyants standards.  
Dans l'hypothèse d'utiliser un produit à base de soude, d'ammoniaque ou d'acide, faire un essai préalable en évitant les inserts.

### DESCRIPTION

Nez de marche en aluminium avec bandes antidérapantes PVC  
Permet de sécuriser les escaliers et de réduire les risques de glissade  
Percé - fraisé : à visser  
18 trous, avec le premier et le dernier à 83 mm  
Les trous sont percés, fraisés puis ébavurés par-dessous  
Inserts disponibles voir catalogue

### USE

Se pose en recouvrement d'un revêtement de sol ou d'un parquet  
Utilisation en intérieur

### REFERENCE

Ref : 1486

### MATERIAL

Profilé aluminium : alliage haut de gamme 6060-T5, N755-2, traité thermiquement pour lui conserver une plus grande dureté. Anodisé 15 micron. Insert antidérapant noir en PVC  
Conformité REACH

### FITTING MODE

Couper le profilé à la longueur souhaitée. Repérer les trous et percer dans la chape. Placer les chevilles ROMUS 94154. Placer le profilé et visser avec les vis 94137. Insérer la bande PVC antidérapante.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :