DATA SHEET

> MAINTENANCE

Utiliser des produits nettoyants standards (détergents neutre)

DESCRIPTION

Plinthe en PVC avec lèvre d'étanchéité co-extrudée
Pour la finition entre un revêtement de mur et un revêtement de sol à coller sur une surface propre et dégraissée
Plinthes décoratives : disponibles en 60, 80 et 100mm Les 12 coloris disponibles en 60mm se marient aux 95% des design de revêtements les plus courants.

USE

Se pose en plinthe
Utilisation en intérieur

REFERENCE

Ref : 2122

MATERIAL

Profilé en PVC co-extrudé. PVC cellulaire semi-rigide teint dans la masse avec un effet décor par impression avec une lèvre d'étanchéité en PVC souple. Couleur : xxxx
Conformité REACH

FITTING MODE

Couper le profilé à la longueur souhaitée. Vous assurer que le support soit bien dégraissé. Appliquer l'adhésif MASTIC COLLE POLYMER ROMUS 93021, ou une colle séche ROMUS type 98220 ou 98230. Mettre le profilé en place en faisant pression.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :