DATA SHEET

> MAINTENANCE

Utiliser des produits nettoyants standards (détergents neutre)

DESCRIPTION

Profilé PVC à coller
Pour la finition entre un revêtement de mur et un revêtement de sol à coller sur une surface propre et dégraissée
A poser après avoir fait la remontée en plinthe. Au besoin refaire une coupe de netteté avec l'araseur «MOLOSS» voir p.102. En PVC rigide et lèvre souple coextrudée pour s'adapter à l'épaisseur du sol PVC.

USE

Se pose en plinthe
Utilisation en intérieur

REFERENCE

Ref : 2413

MATERIAL

Profilé en PVC co-extrudé avec une partie rigide et une lèvre d'étanchéité en PVC souple.
Conformité REACH

FITTING MODE

Couper le profilé à la longueur souhaitée. Vous assurer que le support soit bien dégraissé. Appliquer l'adhésif MASTIC COLLE POLYMER ROMUS 93021. Mettre le profilé en place en faisant pression.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :
Distributor : Tel : Email :