DATA SHEET

DESCRIPTION

Profilé PVC à coller sur une surface propre et dégraissée.
Ce profilé d'Appui Haute Densité permet d'effectuer la remontée en plinthe des sols sur le mur et d'atteindre le classement E3.
Longueur : 2M

USE

Se pose dans l'angle, en dessous du revêtement. Une fois le profilé d'appui et le revêtement de sol installé, la forme arrondie obtenue permet d'éviter les zones de stagnation de particules ou bactéries, facilite le nettoyage avec des pads à la liaison sol/mur, et limite le risque de casser ou percer le revêtement.
Utilisation en intérieur.

REFERENCE

Ref : 2191
APPUI PVC 20X20MM NOIR - 2 M
Qté longueur / boite : 50
Qté ml / boite : 100

MATERIAL

PVC souple de couleur noire. Conformité REACH.
Shore A- 93, pour une pose rapide et une non-déformation du profil.

FITTING MODE

Assurez-vous que le support soit propre et bien dégraissé.
Appliquez une colle double encollage, une colle contact en dispersion ou un adhésif double face de contact type Romtack, compatible avec les profils en PVC.
Mettre ensuite le profilé en place en faisant pression.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :