DATA SHEET

> MAINTENANCE

Pour l'entretien journalier, utiliser des produits nettoyants standards. Dans l'hypothèse d'utiliser un produit à base de soude, d'ammoniaque ou d'acide, faire un essai préalable.

DESCRIPTION

Profilé en inox brossé
Permet de protéger les angles de murs de chocs eventuels avec des chariots, des lits à roulettes
Fixation auto-adhesive VERITAK : colle thermo-fusible qui possède une excellente adhérence, sur une grande variété de support. Tack très élevé et grande souplesse permettant d'absorber des dilatations.
à coller sur une surface propre et dégraissée

USE

Se pose en recouvrement d'un revêtement mural ou du mur peint.
Utilisation en intérieur

REFERENCE

Ref : 2739

MATERIAL

Acier inoxydable d'aspect brossé - Aspect brossé - satiné
Conformité REACH

FITTING MODE

Pose très rapide. Couper le profilé à la longueur souhaitée. Vous assurer que le support soit bien dégraissé. Retirer le papier siliconé. Mettre le profilé en place en faisant pression.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :