DATA SHEET

> MAINTENANCE

Utiliser des produits nettoyants standards (détergents neutre)

DESCRIPTION

Couvre joint aluminium côté adhésif avec clip
Pour couvrir et obturer les joints de dilatation dans les bâtiments industriels, hopitaux, université, centres commerciaux...
Auto-adhésif VERITAK + Fixation par clip de maintien
prévoir environ 5 chevilles 94156 par mètre

USE

Se pose en recouvrement d'un revêtement mural ou du mur peint.
Utilisation en intérieur

REFERENCE

Ref : 28773

MATERIAL

Alliage haut de gamme du genre 6060-T5 – N755-2 traité thermiquement pour lui conserver une plus grande dureté. Anodisé (sans trace de pince de maintien) dans les épaisseurs les plus importantes pratiquées (15 microns). Les couleurs sont celles définies par les normes européennes du "R.A.L.".
Conformité REACH

FITTING MODE

Couper le profilé à la longueur souhaitée. Enfiler le nombre de clips souhaités (un tout les 50 cm). Nous vous conseillons aussi d'utiliser un adhesif MS Polymère. Positioner le profilé et enfoncer le tout en force.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :
Project :
Email :
Tel :

Distributor : Tel : Email :