

DATA SHEET

> MAINTENANCE

Pour l'entretien journalier, utiliser des produits nettoyants standards.
Dans l'hypothèse d'utiliser un produit à base de soude, d'ammoniaque ou d'acide, faire un essai préalable en évitant les inserts.

DESCRIPTION

Nez de marche en aluminium avec bande antidérapante polyuréthane.
Permet de sécuriser les escaliers et de réduire les risques de glissade.

Utilise une bande de 48 mm de largeur et 2 mm d'épaisseur (P.U ou Carborundum).
Bandes antidérapantes à commander à part.

Percé - fraisé : à visser
Dimensions : 68 x 33 mm
Longueur : 4M

USE

Se pose en recouvrement d'un revêtement de sol ou d'un parquet.
Utilisation en intérieur.

REFERENCE

Ref : 1301
NM GT-BORD SIFFLET 68X33-ALU BRUT PERCE- 4 M

MATERIAL

Aluminium Brut. Alliage haut de gamme du genre 6060-T5 – N755-2 traité thermiquement pour lui conserver une plus grande dureté.
Antidérapant : choix de couleurs, voir le catalogue.
Bandes autocollantes en polyuréthane sur support non tissé en polyester imputrescible. Épaisseur : 2 mm. Norme EN14041 (LNE) BF1 S1
Résistance au feu des inserts polyuréthane : Bs2 d0
Conformité REACH

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :

DATA SHEET

FITTING MODE

Coupez le profilé à la longueur souhaitée. Repérez les trous et percez dans la chape. Placez les chevilles ROMUS 94154. Placez le profilé et vissez. Dégraissez le profil aluminium à l'alcool isopropylique avant de poser l'insert. Retirer le papier silicone et coller la bande antidérapante. Marouflez avec roulette 95137.

The information contained in this document is provided for information purposes. Romus cannot be held liable for this information. The user or specifier will check the compatibility of the product technical data with the actual situation. Romus reserves the right to modify all or part of this document without prior notice.

Architect :

Project :

Email :

Tel :

Distributor :

Tel :

Email :