

TECHNICAL DATA SHEET

Safety shoes for floor covering layers

94930:39 94931:40

94932:41 94933:42

94934:43

94935:44

94936:45 94937:46

94938:47



CHERRY S1P SRC

LOW TEXTILE SPORT SHOE



PROTECTION FOR THIS MODEL



Weight of one pair in size 42 (8): 1170 gr.

Norm EN ISO 20345 : 2011 AET: 0075/007/161/07/13/0633

EXT 36/12/13

Upper features

- Upper: tridimensional textile with leather coated
- Tongue: tridimensional textile
- Quarter lining: tridimensional textile
- Vamp lining: synthetic
- Counter: leather board
- Closing : plastic eyelets
- Laces: polyamide in red color
- Tongue marking: size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

Protections

- Toecap: stainless steel (200 joules)
- Midsole: stainless steel (1100 Newtons)

Fitting features

- Natur'form (large)
- Lasting: California Lasting insole: texon
- Footbed: foam and polyurethane

Sole features

- Name: Sporty
- Material: dual density polyurethane
- Comfort sole density: 0,5
- Comfort sole color: dark grey
- Undermine sole density: 1
- Undermine sole color : black
- Slip resistance SRA (flat): 0,49; (heel): 0,37
- Slip resistance SRB (flat): 0,29; (heel): 0,19

Requirements of the norm EN ISO 20345: 2011





Steel midsole Non metallic midsole



A Electric resistance - Antistatic shoes.



CI Insulating sole against cold.



E Heel energy absorption.



FO Hydrocarbons resistance of the undermine sole.



HI Insulating sole against heat.



HRO Heat resistance of the sole.



M Metatarsal protection.



P Perforation resistance.



WRU Water repellent upper. WR Water repellent junction upper/sole.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are: SRA (flat) = 0,32 SRA (heel) = 0,28 SRB (flat) = 0.18SRB (heel) = 0.13

Advantages = End users benefits

Very light and comfortable shoe thanks to the suppleness of the textile

- Tridimentional textile lining, soft and very breathable for better
- Leather coated anti-abrasion on the periphery of the shoe: reduces wear and tear especially when footwear is used in flexion
- Special toe cap (ABG): exclusive LEMAITRE toe cap, asymmetric that matches the shape of the foot for an elegant design and wide for greater interior volume and therefore a better comfort
- → Sporty sole :
 - ✓ Attack heel, for a natural unfolding of the foot during walking and comfort while driving vehicle
 - ✓ Dual density polyurethane (PU2D) injected
 - ✓ Heel shock absorber and very thick sole at the heel for better comfort
 - ✓ Reinforcements of the PU sole at the front and the back of the shoe for a better protection of the leather and the shoe
 - ✓ Cold insulation
 - ✓ Sportive design
 - ✓ Non-slip structure with a studded open for better drainage of fluids
- → Parabolic profile
 - ✓ Exceptional slip resistance: footprint adapts itself to the nature of the ground due to the profile of the sole
 - Spring effect: gives a more dynamic walk
 - Walking assistance: the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate
 - Sporty shape: injection of the PU sole under the foot, enables:
 - Adaptation of the leather to the shape of the foot ✓ Higher breathability of the foot
 - ✓ Flexibility of the sole