



| Pos. | Torque | number of revolutions |
|------|--------|-----------------------|
| 20   | 1,2 Nm | 650 1/min.            |

|  |            |                          |       |  |                |          |
|--|------------|--------------------------|-------|--|----------------|----------|
| Material:                              |            | Volume:                  |       |  |                |          |
| Date                                   | Drawn by   | <b>Triac ST (type A)</b> |       |  |                |          |
| 31.08.2012                             | ha         |                          |       |  |                |          |
| Date                                   | Checked by |                          |       |  |                |          |
| 15.03.2013                             | ha         | Format                   | Scale |  | Drawing number | Revision |
| Leister Technologies AG<br>Switzerland |            | A3                       | %     |  | <b>020.519</b> | <b>B</b> |

This document and its contents are the property of Leister AG. All rights reserved. The use of this document is permitted only for the production of Leister AG products. Any reproduction in any form or by any means, without prior written permission of Leister AG, is prohibited.

**CHALUMEAU ELECTRONIQUE TRIAC ST**  
**Réf. 95078**

| <b>REF</b> | <b>DESIGNATION</b> | <b>REP ECLATEE</b> |
|------------|--------------------|--------------------|
| 97077      | RESISTANCE 142,637 | <b>16</b>          |
| 97211      | CABLE ALIMENTATION | <b>12</b>          |
| 97217      | PAIRE DE CHARBON   | <b>30</b>          |
| 97223      | MANCHON ISOLANT    | <b>18</b>          |
| 97545      | INTERRUPTEUR       | <b>8</b>           |