

## SHEET TECHNIQUE



### **APPLICATION**

Double-sided adhesive tape, ideal for fastening rough floors.

Not resistant to plasticizer

### **Advantages**

#### • **synthetic rubber and resins adhesive:**

- High adherence e
- High level of adhesion on both sides
- Suitable for most types of carpet
- Excellent adhesion to rough surfaces

#### • **Support fabric:**

- Good on different forms
- Can be cut by hand

\* Our products must be tested in real conditions before any industrial use.

The shelf life and storage is 12 months, based on the product stored at 23 ° C and 50% relative humidity in the sun.

### Technical data

Support	Fabric
Adhesive	Rubber and synthetic resins; White
Protective	double-sided silicone paper; Brown
Total thickness (without liner)	0,235 mm
Adhesion to steel	outer face: 35N/25mm inner side:27N/25mm
Strength at break MD	80N/25mm
Elongation at break	15%
Temperature resistance	60°C

Ref.	Type	dimensions
98050	Canvas	50 mm x 5m
98070		50 mm x 25 m
98090		100 mm x 25 m

*Les informations contenues dans ce document sont communiquées à titre indicatif. Elles ne peuvent engager la responsabilité de ROMUS. L'utilisateur ou le prescripteur vérifiera la compatibilité des données techniques du produit avec la situation réelle. La société ROMUS se réserve le droit de modifier tout ou une partie de ce document sans préavis.*

Architecte:

Projet:

Email:

Tél:

Distributeur:

Tél:

Email: