
ROMUS

ROMTACK SKIRTINGS STANDARD Ref. 98215 98220 98235 98230

FICHE TECHNIQUE



TECHNICAL DATA	
Adhesive carrier	Polyester scrim
Adhesive system	Acrylic dispersion
Liner	Silicon paper, brown
Thickness (without liner)	0.22 – 0.24 mm
Peel adhesion	≥ 25 N/25 mm
	(DIN EN 1939)*
Shear adhesion	500 g/625 mm ²
	(DIN EN 1943)*
Processing temperature	+5 °C à +30 °C
Temperature resistance	-20 °C à +80 °C
Condensation water	High
resistance	
Ageing resistance	High
Plasticizer resistance	High
Shelf life	UV-protected, dry,
	room temperature
	(+23 °C)

*The values are based on the applicable norms regarding the testing of adhesive tapes.

DESCRIPTIF

Skirting board adhesive tape with polyester scrim. This product is a double sided, multifunctional adhesive tape.

Super-fast gluing. Neat, no glue residues. Solvent free and odourless. No plasticiser migration. Does not dry out. Extra-long life.

Grammage 250g/m²

Référence	Dimensions
98210	25 mm x 50 m
98215	40 mm x 50 m
98220	50 mm x 50 m
98235	70 mm x 50 m
98230	85 mm x 50 m

USE

For sticking carpet or soft PVC skirtings, as well as PVC cove formers and cove cap skirtings.

MATERIAL

This adhesive film is a highly effective adhesive material from solvent-free and aging resistant polyacrylat with balanced characteristics for adhesive strength and shear strength. A polyester scrim serves as stabilization system.

Polyester fabric support, silicon paper. Peeling DIN EN 1939 > 25N/25 mm. Shearing DIN 1943 500 g/625 mm².