# ROMTACK SKIRTINGS THICK



## DATA SHEET



.

• • • •

ROMUS

TECHNICAL DATA	
Adhesive carrier	Polyester scrim
Adhesive system	Acrylic dispersion
Liner	Silicon paper, brown
Thickness (without liner)	0.44 – 0.46 mm
Peel adhesion	≥ 30 N/25 mm
	(DIN EN 1939)*
Shear adhesion	500 g/625 mm <sup>2</sup>
	(DIN EN 1943)*
Processing temperature	+5 °C à +30 °C
Temperature resistance	-20 °C à +80 °C
Condensation water	High
resistance	
Ageing resistance	High
Plasticizer resistance	High
Shelf life	UV-protected, dry,
	room temperature
	(+23 °C)

\*The values are based on the applicable norms regarding the testing of adhesive tapes.

### DESCRIPTIF

Skirting board adhesive tape with polyester scrim. This product is a double sided, multifunctional adhesive tape.

Dimensions : 35 mm x 50 m Grammage 450g/m<sup>2</sup>

#### USE

For gluing rigid PVC skirtings, or protections mats. Allows you to compensate for wall irregularities.

#### REFERENCE

• 98260 ROMTACK HEAVY DUTY CONTACT ADHESIV TAPE 35MM X 50M

#### MATERIAL

This adhesive film is a highly effective adhesive material from solvent-free and aging resistant polyacrylat with balanced characteristics for adhesive strength and shear strength. A polyester scrim serves as stabilization system.

Polyester fabric support, silicon paper. Peeling DIN EN 1939 > 30N/ 25 mm. Shearing DIN EN 1943 500 g/625 mm<sup>2</sup>.